



## **Forth Ports Limited**

### **Ruling Depths & Under Keel Clearances - Forth**

Vessels are scheduled into / out of ports on the Forth & Tay in accordance with the under keel clearance criteria specified in this section of the Marine Guidelines & Port Information.

Vessel operators who require increased under keel clearance margins, over and above those published in the Marine Guidelines & Port Information must ensure that these requirements are specified to FTNS at the time of booking the vessel's arrival / departure. This is to ensure that vessels are booked for the correct height of tide, and to ensure that delays / impacts to the shipping schedule are avoided.

Agents are advised to ascertain vessel specific under keel clear requirements prior to making arrival / departure bookings through FTNS.

<b>FORTH PORTS LIMITED</b>	Document ID FPS PMSC OP 23/23	Authorised By MM	Original Date January 2014
<b>Ruling Depths &amp; Under Keel Clearances</b>	Date Revised May 2021	Revised By AMM	Review Due May 2022

## LIST OF AMENDMENTS

<b>January 2018</b>	Significant layout changes as well as changes to published depths shown in red
<b>May 2018</b>	Updates to published depths in Leith following recent surveys. Kirkcaldy depths returned to normal following dredge.
<b>June 2018</b>	Hound Point RD 18.6m following survey and review of Grange / Carron dock following first multi beam survey
<b>July 2018</b>	Update to Container Berth depths following Plough dredge.
<b>July 2018</b>	Berth dimensions for all berths in Leith added, changes to some ruling depths in Leith & Rosyth
<b>November 2018</b>	Methil depths updates (all depths now in relation to chart datum)
<b>January 2019</b>	Rosyth ruling depths updated and removal of reference to floating fenders on T Berth
<b>February 2019</b>	Burntisland Key Information Grangemouth J3 & LPG berth depths updated.
<b>May 2019</b>	Leith approach channel remarks & ruling depths within the port Burntisland key information and ruling depths North Imperial cut depth Grangemouth J3 & LPG berths. Methil approach. Rosyth approach
<b>July 2019</b>	Change of UKC for Imperial dock Leith Grangemouth LPG berth Grangemouth Grange Dock- North Grange, North & South Tongue
<b>October 2019</b>	New layout to include the reference chart name and date of the survey Crane pad location added to Rosyth Key information Rosyth ruling depths updated
<b>January 2020</b>	Rosyth ruling depths updated
<b>March 2020</b>	Inverkeithing Harbour depths updated
<b>April 2020</b>	Grange Dock Rosyth North Wall Newhaven Harbour and approaches
<b>August 2020</b>	Grangemouth ruling depth & Rosyth information
<b>December 2020</b>	Rosyth Ruling Depths Removal of berthing details from Fife ports which have been put in MPGI document Kirkcaldy UKC North Imperial Cut – update regarding vessels with LOA of 111m - 119m
<b>May 2021</b>	Grangemouth Ruling Depths Leith Ruling Depths Rosyth Ruling Depths Methil Energy Park Ruling Depths Methil Energy Park Key Information updated

<b>FORTH PORTS LIMITED</b>	Document ID FPS PMSC OP 23/23	Authorised By MM	Original Date January 2014
<b>Ruling Depths &amp; Under Keel Clearances</b>	Date Revised May 2021	Revised By AMM	Review Due May 2022

## GRANGEMOUTH - RULING DEPTHS AND UNDER KEEL CLEARANCE

Data is based on a broad interpretation of current surveys and is only intended as a general guide.

Original surveys should always be consulted especially for detailed operational planning.

The following Ruling Depths apply to the berths, ports and approach channels. The depths indicated are the least depth in the channel or on the berth. Deeper water may be available in certain parts of the channel and conversely shallower water may exist just outside of the channel.

The depths given below are an indication of the least depth, which maybe encountered in the channel, however a close examination of the latest soundings should be made when preparing a passage plan.

**For areas not included in the tables below an under keel clearance of 10% of the vessels maximum draft with a minimum under keel clearance of 0.5m should be used.**

1. Average Grangemouth Dock Density: **1020**
2. Maximum Ship size normally accepted at Grangemouth: **187m \* 27.4m.**
3. All berths in Grange and Carron Dock – average height of quay above waterline **1.0m**
4. Outreach of #4 & #5 transporter cranes **34.5m**, height from quay to gantry **30m.**

### Grangemouth Lock Dimensions

	Overall length	Chamber Length	Max LOA	Width between fenders
Outer	108m	90m	82m	29.1m
Inner	129.6m	112m	104m	
Full	237.6m		187m	

### Grangemouth Berth Dimensions

Berth	Length	Remarks
North Grange 1 - 2	170m	
North Grange 3 - 7	440m	Distance between #7 and #8 is 84m
Tongue N Grange 8 - 11	365m	
Tongue S Grange 12 - 15	365m	
South Grange	630m	
East Wall	215m	
East Cut Width	36m	
West Cut Width	18.3m	
Carron Dry Dock	105m x 16m	Cill 4.8m

<b>FORTH PORTS LIMITED</b>	Document ID FPS PMSC OP 23/23	Authorised By MM	Original Date January 2014
Ruling Depths & Under Keel Clearances	Date Revised May 2021	Revised By AMM	Review Due May 2022

Location	UKC	RD	Remarks	Reference Chart (Name and date of last survey)
<i>Grangemouth Approach Channel</i>	0.6m	6.3 m	In Bellmouth	<b>Grangemouth Bellmouth – Surveyed Monthly</b>
<i>Grangemouth Cill</i>	0.6m	6.0 m		<b>Grangemouth Lock –08.04.20</b>
<b>EASTERN CHANNEL</b>				<b>Eastern Channel</b>
Common User Oil Jetty (Jetty 1 North)	0.3m	10.0 m		31.03.21
Jetty E 1	0.3m	12.1 m	Daughter vessel operations – depth is 10.9m	31.03.21
Jetty E 2	0.3m	10.6 m		31.03.21
Jetty J 2	0.3m	11.1 m		31.03.21
Jetty J 3	0.3m	11.3 m		31.03.21
Jetty J 4	0.3m	7.5 m		31.03.21
EOL LPG Berth	0.3m	8.1 m		31.03.21
East Cut Width = 36 metres	0.5m	8.2m	NB maximum draft for Grange Dock determined by RD at East Cut	31.03.21
<b>GRANGE DOCK</b>				<b>Grange Dock</b>
<b>North</b>				
Grange 1-2 knuckle (Bollard 16-22)	0.3m	7.7m		31.03.21
Grange 3 (13-15 Bollard)	0.3m	7.2m		31.03.21
Grange 3-6 (5-13 Bollard)	0.3m	7.8m	(Bollards 7 & 8 Missing/Out of Use)	31.03.21
Grange 7 (2-5 Bollard)	0.3m	7.3m		31.03.21
<b>Tongue North</b>				
Grange 8 (2-4 Bollard)	0.3m	7.4m		31.03.21
Grange 8-9	0.3m	7.3m		31.03.21
Grange 10-11	0.3m	7.4m		21.01.21
<b>Tongue South</b>				21.01.21
Grange 15	0.3m	5.6m	(Bollard 7 Missing/Out of Use)	
Grange 15 -14	0.3m	6.8m	(Bollard 11 Missing/Out of Use)	
Grange 13-12	0.3m	7.0m		
<b>South</b>				21.01.21
2 – 3.5 Bollard	0.3m	5.5m	Max Draft – 5.2m	
3.5 – 5 Bollard	0.3m	6.8m	Max Draft – 6.5m (Bollard 5 Missing)	
5 – 8 Bollard	0.3m	7.4m	Max Draft – 7.1m (Bollard 5 Missing)	
8 – 15 Bollard	0.3m	8.0m	Max Draft – 7.6m	
15 – 20 Bollard	0.3m	8.7m	Max Draft – 7.7m (dictated by max draft able to pass through the East Cut)	
<b>East Wall</b>				21.01.21
1-8 Bollard	0.3m	7.9m	RD – Restricted by depth on approach to berth.	
<i>Western Channel</i> Maximum ship normally 90m * 14m	0.5m	6.4 m		<b>Western Channel – 31.03.21</b>
<i>West Cut</i> Width = 18.3m	0.5m	7.5 m	For vessels which exceed max. ship dimensions and for dead ship movements detailed planning is required including consultation between Duty Assistant Harbourmaster and Duty Pilot	
<b>CARRON DOCK</b>	0.3m	6.7 m	Max. Ruling depth dictated by the West cut	<b>Carron Dock –11.01.21</b>

<b>FORTH PORTS LIMITED</b>	Document ID FPS PMSC OP 23/23	Authorised By MM	Original Date January 2014
<b>Ruling Depths &amp; Under Keel Clearances</b>	Date Revised May 2021	Revised By AMM	Review Due May 2022

<b>North</b>				
Rankins - no commercial traffic		N/A	Shallows at West End of Berth	
Amsterdam - no commercial traffic		N/A		
Curries - no commercial traffic	0.3m	6.7 m		
Stevens	0.3m	6.6m		
Cross Berth	0.3m	6.4 m	(Between West Cut and Drydock)	
<b>South</b>				
Conveyor & Old Hoist	0.3m	6.8 m		
Watsons Lower	0.3m	6.6 m		
Watsons Middle	0.3m	5.6 m		
Watsons Upper	0.3m	5.0 m	Not in use	
New Quay Wall Lower - Tug Berth	0.3m	5.8 m		
New Quay Wall Upper	0.3m	4.6 m		

<b>FORTH PORTS LIMITED</b>	Document ID FPS PMSC OP 23/23	Authorised By MM	Original Date January 2014
<b>Ruling Depths &amp; Under Keel Clearances</b>	Date Revised May 2021	Revised By AMM	Review Due May 2022

## LEITH - RULING DEPTHS AND UNDER KEEL CLEARANCE

The following Ruling Depths apply to the berths, ports and approach channels. The depths indicated are the least depth which may be encountered in the channel or on the berth. Deeper water may be available in certain parts of the channel and conversely shallower water may exist just outside of the channel. A close examination of the latest soundings should be made when preparing a passage plan.

**For areas not included in the tables below an under keel clearance of 10% of the vessels maximum draft with a minimum under keel clearance of 0.5m should be used.**

1. Data based on a broad interpretation of current surveys and is only intended as a general guide
2. Original surveys should always be consulted; especially for detailed operational planning
3. All Depths quoted are in metres

### Leith Key Information

- Average Dock Density: Leith **1015** (2006 : reported to be 1005)
- Maximum size ship normally accepted at Leith 210m x 30m. Vessels out with these dimensions will be dealt with on a case-by-case basis.
- Lockside is approximately 2m above MHWS.
- Quaysides are approximately 2.2m above dock level and 1.5m at OT the Cruise Liner Berth.

### Leith Lock Dimensions

	Overall length	Max LOA	Width between fenders
Short Lock	92m	85m	31.6m
Intermediate	159m	150m	
Full	259m	210m	

### Leith Dock General Dimensions

Berth	Length	Remarks
Imperial Cut		Entrance width 31.6m
Albert Cut		Entrance width 18.2m
Edinburgh Cut		Entrance width 18.2m
Cruise Liner Berth	375m	
Ocean Terminal	175m	Length of usable quayside ahead of Britannia
West Wall	220m	
Ranks	150m	
North Imperial	570m	
1-4 South Imperial	315m	
5-6 South Imperial	230m	
6 Harbour	150m	
8 – 12 Harbour	305m	
North Side Albert	300m	
4 Albert Cross Berth	85m	
North Edinburgh	440m	
10-13 Edinburgh	290m	
2 Edinburgh	130m	
1 Edinburgh	85m	
Imperial Dry Dock	167.6 x 21.3 x 7.3m	
Edinburgh Dry Dock	91.4 x 12.2 x 5.6m	

<b>FORTH PORTS LIMITED</b>	Document ID FPS PMSC OP 23/23	Authorised By MM	Original Date January 2014
Ruling Depths & Under Keel Clearances	Date Revised May 2021	Revised By AMM	Review Due May 2022

**Caution:** this table is a general summary only. Original sounding surveys are to be consulted for navigation and passage planning.

Location	UKC	RD	Remarks	Reference Chart (Name and date of last survey)
<b>Port of Leith</b>			<b>Sill height 6.71m below ACD</b>	
<i>Leith Approach Channel</i>	1.0m	6.5m	Depths reduce to the west of lock approach. (6.2m R.D 550m North of the Lead in Jetty, known obstruction on the seabed)	<b>Leith Approach Channel – 22.02.21</b>
All Berths except North Imperial	0.5m			
North Imperial	0.4m		With prior agreement from the vessel	
<b>Outer Harbour</b>				<b>Western Harbour – 04.03.21</b>
Common User Oil Jetty		9.4m	Alongside timber structure, otherwise 9.8m. Depths reduce to 8.2m towards Old Imperial Passage. Useable Quay 150m from East End. Max LOA – 120m	
Western Harbour		9.8m to 11.6m	Area South east of West Wall to corner of Ranks and CLB	
		6.5 to 7.2m	Area South of the two Red Buoys	
West Wall		7.7m		
Cruise Liner Berth (Ocean Quay)		10.2m	Reduces 30m from east end	
Ocean Terminal		6.5m		
Ranks Berth		8.3m	<b>No vehicles allowed on wharf.</b> Max Beam = 25m Consult survey chart before berthing on Ranks Berth	
<b>Imperial Dock</b>				<b>Imperial Dock – 04.03.21</b>
Imperial Passage		10.9m	Consult survey chart before berthing in the Imperial Passage.	
North Imperial Cut (Yellow Cranes/ Old Lock)		7.5m	Gantry Clearance 20m (boom down) Maximum length of vessel normally permitted = 110m. Vessels with LOA of 111m - 119m with Harbour Master's approval. Width = 20.3m, Beam = 19m. NOTE: Gate protruding no exit into Western Harbour	
Imperial Dock North		9.4m	Shallows of 9.3m 40m from dry dock	
7 North Imperial		9.5m		
South Imperial (1-2)		9.1m		
South Imperial (3-4)		9.4m	Shallows to 8.4m at extreme eastern end of berth	
South Imperial 5		9.1m		
South Imperial 6		8.4m		
Cross Berth		9.1m	8.5m patch at Southern End Consult survey chart before berthing in the Cross Berth	
<b>Harbour Berths</b>			<b>Fenders required for deep draft vessels.</b>	<b>Outer Harbour – 04.03.21</b>
Head Office Pontoon		2.5m		

<b>FORTH PORTS LIMITED</b>	Document ID FPS PMSC OP 23/23	Authorised By MM	Original Date January 2014
<b>Ruling Depths &amp; Under Keel Clearances</b>	Date Revised May 2021	Revised By AMM	Review Due May 2022

4 Harbour		4.0m	Depths reduce towards Water of Leith Berth only for use by HMS Archer Class	
6 Harbour		7.6m		
8 Harbour		9.5m	Shallows to 8.7m 50m off east of berth	
10 Harbour		9.6m		
12 Harbour		8.5m		
<b>Albert Dock</b>				<b>Albert Dock – 04.03.21</b>
Albert Cut		7.3m		
Albert Dock North – (Measured from East to West) 0m – 230m 230m – West End		8.0m Unknown	Shallows to 7.2m at extreme eastern end Vessel on Berth	
Albert Dock East Wall/Cross Berth		7.0m	Shoaling in Extreme SE corner	
<b>Edinburgh Dock</b>				<b>Edinburgh Dock – 04.03.21</b>
1 Edinburgh (90m)		6.8m		
2 Edinburgh (145m)		7.3m	Max LOA = 100m	
3 Edinburgh (80m)		6.8m		
Edinburgh Dock South Arm – (280m) 10 to 11 Edinburgh 12 to 13 Edinburgh		7.6m 7.5m	Max LOA = 100m	
Edinburgh Dock North Arm (440m)		7.2m	Shallows to 6.8m , 30m from East End	

<b>FORTH PORTS LIMITED</b>	Document ID FPS PMSC OP 23/23	Authorised By MM	Original Date January 2014
<b>Ruling Depths &amp; Under Keel Clearances</b>	Date Revised May 2021	Revised By AMM	Review Due May 2022



## ROSYTH & FIFE PORTS – RULING DEPTHS AND UNDER KEEL CLEARANCE

The following Ruling Depths apply to the berths, ports and approach channels. The depths indicated are the least depth in the channel or on the berth. Deeper water may be available in certain parts of the channel and conversely shallower water may exist just outside of the channel. A close examination of the latest soundings should be made when preparing a passage plan.

**For areas not included in the tables below an under keel clearance of 10% of the vessels maximum draft with a minimum under keel clearance of 0.5m should be used.**

1. Data based on a broad interpretation of current surveys and is only intended as a general guide
2. Original surveys should always be consulted; especially for detailed operational planning
3. All Depths quoted are in metres.

### Rosyth

#### Rosyth Key Information

- Height of quayside above CD is 7.522m
- Maximum length normally accepted at the North Wall is 250m. Vessels out with these dimensions, and for all other berths, will be dealt with on a case-by-case basis.
- Rosyth traffic is subject to aircraft restrictions due to the Forth Bridges. Ref: Marine Procedure, Guidelines and Information section 1.1
- North Wall strengthened quay 200-400m marks – operating area for the Liebherr crane

Berth	Length	Remarks
North Wall	540m	450m fendered at 15m intervals from the west end. White rectangle painted at 530m mark. Berth Box = 35m wide.
T Berth	220m	Ferry berth with Links-span 143m of quayside ahead of the linkspan Fixed Fenders – Protrude 3.7m to seaward and 2m above quayside.
S	160m	
R	170m	
Q	150m	
P	150m	Small pontoon in NE corner
O	170m	

**Caution:** this table is a general summary only. Original sounding surveys are to be consulted for navigation and passage planning.

Location	UKC	RD	Remarks	Reference Chart (Name and date of last survey)
<b>Rosyth Approach Channel</b>	0.5m	8.1m	Depths reduce to 7.9m between buoys No 3 & No 4.	<b>Rosyth Approach</b> – 18.02.21
<b>Rosyth Swing Area</b>	0.5m	8.0m		20.01.21
<b>Port of Rosyth</b>				
North Wall 0-30m 30 –450m	0.5m	6.0m 8.8m	8.7m spot @ 220m White rectangle at 530m.	<b>Port of Rosyth</b> – 16.03.21
T Berth		8.1m	7.9m on approach	<b>Port of Rosyth</b> – 18.02.21
S Berth		2.6m	In-line with the linkspan then it shelves	
Approaches to OPQR berths		3.1m	Shallows to 2.1m South East of No.5a Buoy	
O Berth		3.9m		<b>Port of Rosyth</b> – 20.01.21
P Berth		3.5m		

<b>FORTH PORTS LIMITED</b>	Document ID FPS PMSC OP 23/23	Authorised By MM	Original Date January 2014
<b>Ruling Depths &amp; Under Keel Clearances</b>	Date Revised May 2021	Revised By AMM	Review Due May 2022

Q Berth		4.4m		
R Berth		4.6m	4.2m shallow spot approx 38m from the North end	

## **Babcock**

<b>Babcock – consult H.M for latest information</b>	0.6m		N.B. UKC for warships = 1.0m.	
Non Tidal Basin		9.7m	Basin maintained CD + 4.2m.	<b>Main Basin – 08.01.19</b>
Middle Jetty N		4.0m	Shallows to West	<b>Swinging Areas and Berths – 02.12.20</b>
Middle Jetty S		6.4m		<b>Swinging Areas and Berths – 02.12.20</b>
South Arm		8.4m	Fenders required to find deepest water in dredged box	<b>Swinging Areas and Berths – 02.12.20</b>
Approaches to Direct Entrance		6.3m		<b>Swinging Areas and Berths – 02.12.20</b>
Sills (Lock and Direct Entrance)		6.57m		

<b>FORTH PORTS LIMITED</b>	Document ID FPS PMSC OP 23/23	Authorised By MM	Original Date January 2014
<b>Ruling Depths &amp; Under Keel Clearances</b>	Date Revised May 2021	Revised By AMM	Review Due May 2022

## Burntisland

### Burntisland Key Information

- Entrance to harbour between breakwaters is 76m wide.
- Maximum size ship normally accepted at the East Dock 100m x 16m. Vessels out with these dimensions will be dealt with on a case-by-case basis.
- Maximum size ship normally accepted at the West dock 100m x 27m.
- An estimated water loss of up to 1m per tide can be experienced in the East dock while the West dock can lose up to 0.5m per tide.
- West dock based on an impounded dock height of 4.48m

Berth	Width	Remarks
Entrance to East Dock	18.2m	Sill height 3.09m below CD – mitre gate.
Entrance to West Dock	29.5m	Sill height 0.81m below CD – folding gate

**Caution:** this table is a general summary only. Original sounding surveys are to be consulted for navigation and passage planning.

Location	UKC	RD	Remarks	Reference Chart (Name and date of last survey)
<b>Burntisland</b>				<b>Burntisland Approach – 19.03.20</b>
Outer Approaches	0.5m	3.6m		
East Dock Approach		2.4m	Consideration to be given to the shallow water west of the east dock approach during inclement weather or during approach manoeuvres	<b>Burntisland Outer Harbour – 19.03.20</b>
East Dock		2.1m		
No1 Berth – West		2.7m		
No2 Berth - East		2.6m		
West Dock Approach		-0.3m		
West Dock west wall		4.98m	Shoals 0.6m from quay face fenders required to remain clear of this	
North/East/South wall			Consult sounding chart – area leased to Briggs marine	

<b>FORTH PORTS LIMITED</b>	Document ID FPS PMSC OP 23/23	Authorised By MM	Original Date January 2014
Ruling Depths & Under Keel Clearances	Date Revised May 2021	Revised By AMM	Review Due May 2022

## Methil

### Methil Key Information

- Main Entrance to No.2 Dock is 15.2m wide
- Maximum size vessel normally accepted is 100m x 14.0m beam. Vessels out with these dimensions will be dealt with on a case-by-case basis.
- Dock gates normally open three hours before high water.
- Depth over the outer sill (No.2 dock) is 2.6m below chart datum (No.1 dock is 1.22m above the sill at No.2)

Berth	Length	Remarks
<b>Number 2 Dock</b>		15.2m wide, sill 2.6m below ACD
Cross berth	85m	
No.1 (Hard Pad)	130m	
No.2 (Central Farmers)*	82m	
NE Corner	213m	Travelling crane
No.6		
Distance across dock between Hard Pad and South side is 121m		
Distance across dock between Central Farmers and South side is 109m		
<b>Number 1 Dock</b>		
South side	173m	
North side	136 + 58m	
West (North)	43m	
West (South)	43m	
East side	82m	
Distance across dock North to South side is 103m		

**Caution:** this table is a general summary only. Original sounding surveys are to be consulted for navigation and passage planning.

Location	UKC	RD	Remarks	Reference Chart (Name and date of last survey)
<b>Methil Approaches</b>	1.0m	0.8m	Shallows along outer West pier end	<b>Methil Harbour – 20.05.20</b>
Methil Berths (within No.2 dock)	0.5m			<b>Methil Harbour – 20.05.20</b>
Cross/Stone Berth		1.5m		
#1 (Hard Pad)		1.6m	Patch of 1.2m on approach	
#2 (Central Farmers)		1.7m		
North East Corner		1.7m		
#6		1.4m		

<b>FORTH PORTS LIMITED</b>	Document ID FPS PMSC OP 23/23	Authorised By MM	Original Date January 2014
<b>Ruling Depths &amp; Under Keel Clearances</b>	Date Revised May 2021	Revised By AMM	Review Due May 2022

## Methil Energy Park

### Methil Energy Park Key Information

- Berths owned by Scottish Enterprise
- Maximum sized barges/vessels dictated by draft & mooring analysis carried out by tenant

For further information, please refer to latest edition of Energy Park Fife Quayside Regulations.

Berth	Length	Remarks
East Quay 1	184m	Mooring dolphins & offshore mooring buoys used
West Quay 2	178m	140m of surveyed quayside

**Caution:** This table is a general summary only. Original sounding surveys are to be consulted for navigation and passage planning.

Location	UKC	RD	Remarks	Reference Chart (Name and date of last survey)
<b>Methil (Energy Park Fife)</b>	0.5m			<b>Methil BiFab – 07.08.18</b>
East Berth (Quay 1) 0 to 70m 70 – 100m 100 – 180m	0.5m	1.6m 3.0m 3.7m	With stand-off fendering. Distance given from northern end of East Berth Quay 1.	
West Berth (Quay 2) 0 to 80m 80 - 140m	0.5m	3.2m 3.9m	With stand-off fendering. Distance given from corner of Quay 1 and Quay 2. A patch of 3.4m exists 25m off the berth at the 30m mark.	

## Kirkcaldy

### Kirkcaldy Key Information

- Main entrance is 15.2 wide.
- Sill height 0.65m below Chart datum.
- Maximum size vessel normally accepted is 85m x 14m. Vessels out with these dimensions will be dealt with on a case by case basis.
- Port Side is the preferred side alongside at Carrs Milling.
- The berth is a NAABSA Berth (Not Always Afloat but Safely Aground).
- Lock gates are no longer in use.

Berth	Length	Remarks
NE Berth	Max Vessel 85m	

**Caution:** this table is a general summary only. Original sounding surveys are to be consulted for navigation and passage planning.

Location	UKC	RD	Remarks	Reference Chart (Name and date of last survey)
<b>Kirkcaldy</b>				<b>Kirkcaldy Harbour – 02.03.21</b>
Approaches	0.5m	-0.2m	Area subject to siltation – latest sounding chart to be consulted.	
Inner Harbour	0.4m	-0.3m		
NE Berth	0.4m*	0.5m		
* Vessels usually take bottom and stated to be NAABSA Berth (Not Always Afloat but Safely Aground). by the berth operators – stated UKC are for berthing operations				

<b>FORTH PORTS LIMITED</b>	Document ID FPS PMSC OP 23/23	Authorised By MM	Original Date January 2014
Ruling Depths & Under Keel Clearances	Date Revised May 2021	Revised By AMM	Review Due May 2022

## Inverkeithing

### Inverkeithing Key Information

- Berths in Inverkeithing are managed by either RM Recycling or Forth Bridge Stevedoring Limited.
- All berths designated NAABSA by berth operators.

Berth	Length	Remarks
Deepwater Berth	130m	Max vessel length 110m
No 1 Berth	140m	
No 2 + No 3 Berths		Berths not used for commercial traffic
Stone Berth (Quarry)	30m	Max LOA 110m
Old Sea Plane Berth		Berth not used for commercial traffic
East Ness Berth	20m	Max vessel LOA = 100m

**Caution:** this table is a general summary only. Original sounding surveys are to be consulted for navigation and passage planning.

Location	UKC	RD	Remarks	Reference Chart (Name and date of last survey)
<b>Inverkeithing Approaches</b>	0.5m	0.4m		<b>Inverkeithing Approach – 20.11.19</b>
<b>Inverkeithing</b>				<b>Inverkeithing Harbour – 25.03.20</b>
Deep Water Berth	*0.3m	1.0m	Restricted to 0.4m owing to approaches: consult sounding chart for depths alongside berth.	
No 1	*0.3m	-2.0m	Shoals 20m north of berth,	
Stone Berth (Quarry)	*0.3m	0.2m	PST preferred.	
East Ness Berth	*0.3m	-0.2m	Maximum LOA 100m.	
* Vessels usually take bottom and stated to be “Not Always Afloat But Safe Aground” (NAABSA) by the berth operators – stated UKC are for berthing operations				

## Hound Point

Location	UKC	RD	Remarks	Reference Chart (Name and date of last survey)
HP 1 and HP2	2.1m	18.6m	See marine guidelines & Port Information for calculating maximum draft.	<b>Hound Point Oil Terminal – 08.05.18</b>

## Braefoot

	UKC	RD	Remarks	Reference Chart (Name and date of last survey)
				<b>Mortimers Deep – 16.09.20</b>
East Out	2.0m	10.0m	See Braefoot Tide tables.	
West Out	2.5m	10.5m	See Braefoot Tide tables.	

## Crombie

Location	UKC	RD	Remarks	Reference Chart (Name and date of last survey)
South Jetty	1.0m	12.0m	Reported by DM Crombie	Aspect A6668 <b>DM Crombie – 15.06.18</b>
North Jetty	1.0m	7.5m		Aspect A6668 <b>DM Crombie – 15.06.18</b>

<b>FORTH PORTS LIMITED</b>	Document ID FPS PMSC OP 23/23	Authorised By MM	Original Date January 2014
<b>Ruling Depths &amp; Under Keel Clearances</b>	Date Revised May 2021	Revised By AMM	Review Due May 2022

## Newhaven

Location	UKC	RD	Remarks	Reference Chart (Name and date of last survey)
Newhaven Anchorage	0.5m	8.0m	Depths increase to Eastern end of anchor area	<b>Leith Roads – 14.05.18</b>
				<b>Newhaven – 01.03.21</b>
Newhaven Approaches	0.3m	1.0m	Area subject to siltation, consult latest sounding chart	
Newhaven Harbour	0.3m	1.0m	Area subject to siltation, consult latest sounding chart	

<b>FORTH PORTS LIMITED</b>	Document ID FPS PMSC OP 23/23	Authorised By MM	Original Date January 2014
<b>Ruling Depths &amp; Under Keel Clearances</b>	Date Revised May 2021	Revised By AMM	Review Due May 2022